DURASTONE Flexible Polished Floors
Maintenance

General recommendations:
- It is highly recommended to place a quality doormat which has a scraping and drying function at the entry of the building.
- Sand and dirt have an abrasive effect and should be collected as much as possible.
- You can prevent scratch and trail tracks as much as possible by keeping the finish in good state.

Daily maintenance:
- Durastone can be primarily cleaned with a vacuum cleaner in most cases.
- Remove dust with a dust wiper.
- Prevent sharp pollution like broken glass, stones and gravel.

Periodical wet maintenance dependent of pollution and contamination:
- Wet mop the floor and remove contaminated water.
- Possible use scrubber with soft brushes or white pad.
- Use a non-film forming cleaning agent.

Repairs:
In case of heavy mechanical damage, the Durastone damaged area can be cut from the floor. Afterwards a new drop of Durastone can be used to fill the hole.

Cleaning agent for wet cleaning:
Use a neutral detergent without film formation.



Instructions:
For heavy soiling: Dilute 1:25-1:30 (1 part cleaner and 25-30 parts water) in cold water. Apply this solution to the floor with a mop or scrubbing machine and let it work in for about 5 minutes. Work the solution again, i.e. “move” and remove with a wet vacuum cleaner or puller. Normal cleaning: Dilute 1:50-1:60 (1 part cleaner and 50-60 parts water).

Duracryl International BV
Elandstraat 91
2901 BK Capelle aan den IJssel
Tel. +31 (0) 10 - 450 52 31
Fax +31 (0) 10 - 451 24 69
www.duracryl.com
info@duracryl.com